

# BRW350\* Air Cooled Remote BRW360\* Water Cooled Range



The High Performance [BRW350\\*](#) Air Cooled and [BRW360\\*](#) Water Cooled Remote Cooler Range develops 25kgs of ice with impressive recovery times. The unit can be factory configured for use with glycol based coolants for extra cold applications with thermostat, pump and coil pack variants available.



- Customer driven design features
- Designed-in performance enhancements to meet all demands and working environments
- Ideal for a range of applications - to suit the demand and length of python
- First-class build quality, robust construction and attractive finish
- Improved access to components for easier maintenance and on-site servicing
- Complementary models included in the range



Available with the new [HDU301](#) 3-Pass Universal Heat Dump Unit with a removable Condenser Cartridge, accessible from both sides, has been developed for the ease of installation, its light weight configuration is ideal for any site. Its impressive interchangeability makes it an ideal cost saving package.

# BRW350\*Air Cooled Remote BRW360\*Water Cooled Range



## SPECIFICATIONS

<b>Dimensions &amp; Weight</b>	
Height (incl. pump & casters)	900 mm
Width (incl. handles)	580 mm
Depth (incl. overflow & spacers)	630 mm
Dry Weight	65 kg BRW350 / 70 kg BRW360
<b>Operating Parameters</b>	
Electrical	230 V~ 50 Hz, 10 Amps
Aux. Output (BRW360)	24 V AC 120kVA
Ambient Temperature	5 °C to 32 °C
<b>Refrigeration &amp; Cooling System</b>	
Compressor Size	21 cc
Refrigerant (& charge)	R134a (320 g)
Cooling Power @ 32° Ambient	1.5 kW
Condenser Fan Power	16 W (output)
Icebank	25 kg nominal
Icebank Control	Mechanical or Digital
Water Bath Capacity	65 ltr
Recirculation Pump	Totton SPC 2, 3 or 4 stage Pump
Glycol Recirculation Pump (BRW360)	Totton 20/18
<b>Water &amp; Product Coil Specifications</b>	
Number of Product Coils	Up to a maximum of 14
Product Coil Lengths (dia)	316 stainless length variants

Options: - \*

- Single or Twin Thermostat Water Bath Control
- Mechanical or Digital Icebank Control
- Totton SPC 2, 3 or 4 stage Recirculation Pump
- Air Cooled or Water Cooled
- One Piece Lid with Filler Cap or Two Piece Lid with Inspection Panel
- 1.5 Short, 3.8 Std, 5.0 Long, 8.0 Ex Long or 10.0mtr Super Long Coils