

EXL1250* Air Cooled Remote EXL1260* Water Cooled Range



The High Performance **EXL1250*** Air Cooled and **EXL1260*** Water Cooled Remote Cold Carbonator Unit develops 25kgs of ice with impressive recovery times. This unit contains an integral 3.4L Carbonator Vessel situated in the 65L Water Bath. The system features a removable top deck for ease of installation and up to 8 optional product coils. The **EXL1260*** houses a glycol tank and pump internally creating a 2 part system. The unit has been designed for effective performance and improved energy efficiency.

Built for durability and reliability, the **EXL1250*** & **EXL1260*** achieve optimum dispense-point temperatures by combining its efficient refrigeration system with a submerged carbonator vessel and “through the bowl” recirculation.

The **EXL1250*** & **EXL1260*** offer maximum flexibility with easy access to all serviceable components, quicker install times with push fit bulkhead connectors and the most powerful in its class Rotary Vane Pump and Electric Motor to recirculate the carbonated water more effectively and minimise heat absorption

Customer driven design features
Designed-in performance enhancements to meet all demands and working environments
Ideal for a range of applications – especially remotely-sited high volume accounts
First-class build quality, robust construction and attractive finish
Improved access to components for easier maintenance and on-site servicing
Complementary models included in the range



EXL1250*Air Cooled Remote EXL1260*Water Cooled Range



SPECIFICATIONS

Dimensions & Weight	
Height	600 MM
Width (incl. handles)	900 MM
Depth – 1250 / 1260	525 MM / 640 MM (incl. spacer & tank)
Dry Weight – 1250 / 1260	76 KG / 82 KG
Operating Parameters	
Electrical	230 V~ 50 Hz, 8 Amps
Aux. Output – 1260	24 V AC 120 VA
Ambient Temperature	5 °C to 32 °C
Refrigeration & Cooling System	
Compressor Size	21.0 CC
Refrigerant (& charge)	R134a (370 G)
Cooling Power @ 32° Ambient	570 W
Compressor Cooling Fan	10 W
Icebank	25 KG
Water Bath Capacity	65 LTR
Recirculation Pump	S/S RV Pump & Motor
Water & Product Coil Specifications	
Python Pre-chill Coil Length (dia)	10 M (3/8")
Soda Pre-chill Coil Length (dia)	10 M (3/8")
Still Water Coil Length (dia)	4 M (3/8")
Number of Product Coils	8 Maximum
Product Coil Lengths (Optional)	2 M (3/8")