

EXL550 Soda Recirc Cooler



The **EXL550 SR** cooler is designed for effective performance and improved energy efficiency. Utilising a 15-litre water bath, the **EXL550 SR** develops a 5.0 kg icebank reserve for optimum performance.

Built for durability and reliability, the **EXL550 SR** achieves optimum dispense-point temperatures by combining its efficient refrigeration system with a unique and optimised coil-pack design



The **EXL550 SR** offers longer bath coils to maximise capacity and performance, and uses a powerful 6/8 re-circulation pump to recirculate the carbonated water more effectively and minimise heat absorption.

- Customer driven design features
- Designed-in performance enhancements to meet all demands and working environments
- Ideal for a range of applications - especially remotely-sited or undercounter installations
- First-class build quality, robust construction and attractive finish
- Improved access to components for easier maintenance and on-site servicing
- Complementary models included in product range



booth
innovation in cooling



SPECIFICATIONS

Dimensions & Weight	
Height	290mm
Width (Incl. Handles)	630mm
Depth (Incl. Spacer & overflow)	470mm
Dry Weight	28.0kg
Operating Parameters	
Electrical Supply	230 V~ 50 Hz, 5 Amp
Ambient Temperature	5°C to 32°C
Refrigeration & Cooling System	
Compressor Size	6.0cc
Refrigerant (& charge)	R134a (125g)
Cooling Power	375w
Condenser Fan Power	44w
Icebank	5.0kg
Water Bath Capacity	15ltr
Recirculation Pump	Totton 6/8
Water & Product Coil Specifications	
Python Pre-chill Coil Length (dia)	3.45mtr (3/8")
Soda Pre-chill Coil Length (dia)	2.90mtr (3/8")
Still Water Coil Length (dia)	1.60mtr (5/16")
Number of Product Coils	4
Product Coil Lengths (dia)	1.11, 1.02, 0.93, 0.82mtrs (5/16")

