

HDU301 Heat Dump Unit



The **HDU301** 3-Pass Universal Heat Dump Unit with a removable Condenser Cartridge, now accessible from both sides, is designed for effective performance and improved design.

The **HDU301** has been developed for the ease of installation, its light weight configuration is ideal for any site. Its impressive interchangeability makes it an ideal cost saving package for the quick fit replacement of any parts on site, from the Condenser which can be installed or removed from either side down to the Push-in Electrical Connections.



Built for durability and reliability, the pull out Condenser Cartridge saves you time and the cost of a complete new replacement on site. This space saving design incorporates standard trade fittings and easy key-hole access panels. With Universal Fixing Bracket to replace existing models in trade.

- Customer driven design features
- First-class build quality, robust construction and attractive finish
- Lightweight for ease of installation
- Pull out replacement Condenser Cartridge
- Condenser Cartridge accessible from either side
- Easier maintenance and on-site servicing
- Universal fixing points and service fittings
- Improved access to components for interchangeability
- Push-in Electrical Connections
- Complementary models included in product range

HDU301 Heat Dump Unit



SPECIFICATIONS

Dimensions & Weight	
Height	425mm
Width (not including handle)	480mm
Depth	330mm
Cartridge Only Dry Weight	6.0 Kg
Fan & Frame Only Dry Weight	7.5 Kg
Complete Unit Dry Weight	13.5 Kg
Operating Parameters	
Electrical	24 V – 50 Hz, 3.9 Amps
Rated Current	5.5A
Cooling System	
Condenser Fan Input	60 W
Condenser Fan Output	24 v – 16 W
Water Coil Specifications	
Condenser Product Coil	3 – Pass
Product Coil Connection	15 mm
Heat Dump Noise Emissions (@1m)	60 Db

