



- Customer driven design features
- First-class build quality, robust construction and attractive finish
- Designed-in performance enhancements to meet all working environments
- Improved access to components for easier maintenance and on-site servicing



TRM9HC
Shelf Cooler
(Dry Block)

TRM9HC Dry block cooler does not require water or ice and delivers consistent dispense temperatures within a few minutes of start-up.

The TRM9HC refrigeration system is fitted with digital control for all types of drink dispense and is designed for effective performance and improved energy efficiency. The TRM9HC utilises aluminum block technology and demonstrates excellent recovery times typically less than a minute. The unit is ideal for mobile bars or secondary cooling and is configured for use on single product with an option for two depending on the targeted beer temperature.

Built for durability and reliability, the TRM9HC achieves optimum dispense-point temperatures by combining its efficient refrigeration system with an optimised heat exchanger design achieving consistent beer temperatures with a Delta-T of up to 20 (Deg-C) from incoming beer at 24 (Deg-C) or ambient temperature.

| Dimensions & Weight | |
|-------------------------------------|-----------------------|
| Height | 260 mm |
| Width (incl. handles) | 470 mm |
| Depth (incl. spacer & overflow) | 425 mm |
| Dry Weight | 30 kg |
| Operating Parameters | |
| Electrical | 230 V~ 50 Hz, 10 Amps |
| Ambient Temperature | 5 °C to 32 °C |
| Refrigeration & Cooling System | |
| Compressor Size | Cubigel NLY12RAa |
| Refrigerant (& charge) | R290 |
| Cooling Power | 600 W |
| Condenser Fan Power | 10 W |
| Water & Product Coil Specifications | |
| Number of Product Coils | 1 (+1) |



Brandels - A Division of Booth Dispensers Limited
Moor Park Avenue, Blackpool, Lancashire, FY2 0LZ
T: +44 (0)1253 501800 - sales@brandels.co.uk