



- Ideal for a range of applications, compact size ideally suited to under-counter installations
- Designed in performance enhancements to meet all demands and working environments
- First-class build quality, robust construction and attractive finish
- Designed to operate in environments with temperatures up to 32° C and high air humidity



BRW17H
High Performance Mini
Remote Cooler Range

The New BRW17H Mini Remote Cooling Unit is small and versatile; it can be floor sited on castors or wall mounted with brackets (supplied optional). With improved twin fan and evaporator design, for effective performance giving optimum recovery and producing maximum cooling from the refrigeration system.

The unit incorporates level indicator on the front of the unit to observe water bath level, with the added benefit designed for draining the unit. Optional range of top mounted water recirc pumps, to suit the length of python. Large filling hole for easier access to fill or top up. The unit can be factory configured for use with glycol-based coolants for extra cold applications.

Dimensions & weights	
Height (incl. pump)	735mm
Width (incl. Handles)	451mm
Depth (incl.overflow)	371mm
Dry Weight	Nominal 30Kg
Operating Parameters	
Electrical	230Vac/50Hz
Ambient Temperature	SN (Subnormal: +10°C to +32°C)
Refrigeration & cooling System	
Compressor Size	8.1cc
Charge	70g
Power consumption	627W
Cooling Power (24°C)	596 W
Ice bank	10Kg
Ice Bank Control	Digital, Energy Save or Mechanical
Water Bath Capacity	25L
Recirculation Pump	3 Stage or 4 Stage Pump
Water & Product Coil Specification	
Number of product coils	0,2,3,4,5 or 6
Product Coil Lengths (dia)	Each coil is 4m - (5/16")

Options

- Thermostat – Mechanical, Digital or Energy Save
- 3 or 4 Stage Recirc Pump
- Up to 6 Product Coils can be supplied as a 2, 3, 4, 5 or 6 Configuration



Brandels - A Division of Booth Dispensers Limited
Moor Park Avenue, Blackpool, Lancashire, FY2 0LZ
T: +44 (0)1253 501800 - sales@brandels.co.uk