



- Ideal for a range of applications, compact size ideally suited to under-counter installations
- Designed in performance enhancements to meet all demands and working environments
- First-class build quality, robust construction and attractive finish
- Designed to operate in environments with temperatures up to 32° C and high air humidity



BRW1HA3 High Performance Python Temperature Control Cooler

The New BRW1HA3 Cooling Unit is small and versatile; it can be floor sited or wall mounted with brackets supplied. With improved twin fan and evaporator design, for effective performance giving optimum recovery and producing maximum cooling from the refrigeration system.

The electronic digital thermostat, offers an accurate temperature control ranges from -10 to +15 degrees, also provides you with a constant visible read out to the point of a degree. Incorporates level indicator on the front of the unit to observe the water bath level, with the added benefit designed for draining the unit. Optional range of top mounted water re-circ pumps, to suit the length of python. Large filling hole for easier access to fill or top up.

Dimensions & weights	
Height (incl. pump)	705mm
Width (incl. Handles)	451mm
Depth (incl.overflow)	371mm
Dry Weight	Nominal 30Kg
Operating Parameters	
Electrical	230Vac/50Hz
Ambient Temperature	SN (Subnormal: +10°C to +32°C)
Refrigeration & cooling System	
Compressor Size	4.5cc
Charge	70g
Power consumption	485W
Cooling Power (24° C)	425 W
Ice bank	N/A
Ice Bank Control	Digital, Energy Save or Variable Mechanical
Water Bath Capacity	25L
Recirculation Pump	3 Stage or 4 Stage Pump
Water & Product Coil Specification	
Number of product coils	N/A
Product Coil Lengths (dia)	N/A

Options

- Thermostat – Digital, Energy Save or Variable Mechanical
- 3 or 4 Stage Recirc Pump



MADE IN THE UK



Brandels - A Division of Booth Dispensers Limited
Moor Park Avenue, Blackpool, Lancashire, FY2 0LZ
T: +44 (0)1253 501800 - sales@brandels.co.uk