



- Designed-in performance enhancements to meet all working environments
- Ideal for a range of applications especially remotely-sited or under counter installations
- First-class build quality, robust construction and attractive finish
- Improved access to components for easier maintenance and on-site servicing



EXL550
Soda Recirc
Shelf Cooler

The EXL550 SR cooler is designed for effective performance and improved energy efficiency. Utilising a 15-litre water bath, the EXL550 SR develops a 5.0 kg ice bank reserve for optimum performance.

Built for durability and reliability, the EXL550 SR achieves optimum dispense point temperatures by combining its efficient refrigeration system with a unique and optimised coil-pack design.

The EXL550 SR offers longer bath coils to maximise capacity and performance, and uses a powerful 6/8 re-circulation pump to recirculate the carbonated water more effectively and minimise heat absorption.

Dimensions & Weight	
Height	290mm
Width (Incl. Handles)	630mm
Depth (Incl. Spacer & overflow)	470mm
Dry Weight	28.0kg
Operating Parameters	
Electrical Supply	230 V~ 50 Hz, 5 Amp
Ambient Temperature	5°C to 32°C
Refrigeration & Cooling System	
Compressor Size	6.0cc
Refrigerant (& charge)	R134a (125g)
Cooling Power	375w
Condenser Fan Power	44w
Icebank	5.0kg
Water Bath Capacity	15ltr
Recirculation Pump	Totton 6/8
Water & Product Coil Specifications	
Python Pre-chill Coil Length (dia)	3.45mtr (3/8")
Soda Pre-chill Coil Length (dia)	2.90mtr (3/8")
Still Water Coil Length (dia)	1.60mtr (5/16")
Number of Product Coils	4
Product Coil Lengths (dia)	1.11, 1.02, 0.93, 0.82mtrs (5/16")



Brandels - A Division of Booth Dispensers Limited
Moor Park Avenue, Blackpool, Lancashire, FY2 0LZ
T: +44 (0)1253 501800 - sales@brandels.co.uk