

NEW



- A cold carbonation unit with constantly cooled soda water and impressive carbonation levels
- Ideal for a range of applications especially remotely-sited or undercounter installations
- Improved access to components for easier maintenance and on-site servicing
- The unit easily fits on bar, café and restaurant counters. Perfect for where areas with limited space



EXL65HC
High Performance
Cooler Carbonator

Our latest edition to the R290 hydrocarbon range of coolers the EXL65HC cooler carbonator is designed for effective performance and improved energy efficiency. Utilising a 15-litre water bath, the EXL65HC develops a 6.5 kg icebank reserve for optimum performance. Built for durability and reliability, the EXL65HC achieves optimum dispense-point temperatures by combining its efficient refrigeration system with a unique and optimised coil-pack design.

The EXL65HC Cooler Carbonator provides a reliable supply of cold carbonated water

Dimensions & weights	
Height (incl. pump)	299mm
Width (incl. Handles)	655mm
Depth (incl.overflow)	455mm
Dry Weight	Nominal 36Kg
Operating Parameters	
Electrical	230Vac/50Hz
Ambient Temperature	SN (Subnormal: +10°C to +32°C)
Refrigeration & cooling System	
Compressor Size	5.98cc
Charge	65g
Power consumption	350w
Cooling Power (24°C)	286W
Icebank	6Kg
Ice Bank Control	Eliwell/Dfx/Mechanical
Water Bath Capacity	15 litres
Recirculation Pump	Totten HPR6/11
Water & Product Coil Specification	
Number of product coils	0, (4 coil Pack available)
Product Coil Lengths (dia)	Each coil is 1.85m - (5/16")
Carb Can Spec	
Carb Can Volume	1.385 Litres



Brandels - A Division of Booth Dispensers Limited
 Moor Park Avenue, Blackpool, Lancashire, FY2 0LZ
 T: +44 (0)1253 501800 - sales@brandels.co.uk