

NEW



- Ideal for a range of applications especially remotely-sited or undercounter installations
- Improved access to components for easier maintenance and on-site servicing
- The unit easily fits on bar, café and restaurant counters. Perfect for where areas with limited space
- First-class build quality, robust construction and attractive finish



EXL65HX
High Performance
Remote Soda Recirc Cooler

Our latest edition to the R290 hydrocarbon range of coolers the EXL65HX cooler is designed for effective performance and improved energy efficiency. Utilising a 15-litre water bath, the EXL65HX develops a 6.5 kg icebank reserve for optimum performance. Built for durability and reliability, the EXL65HX achieves optimum dispense-point temperatures by combining its efficient refrigeration system with a unique and optimised coil-pack design. The EXL65HX offers longer bath coils to maximise capacity and performance, and uses a powerful 6/11 re-circulation pump to recirculate the carbonated water more effectively and minimise heat absorption.

Dimensions & weights	
Height (incl. pump)	299mm
Width (incl. Handles)	655mm
Depth (incl.overflow)	455mm
Dry Weight	Nominal 26Kg
Operating Parameters	
Electrical	230Vac/50Hz
Ambient Temperature	SN (Subnormal: +10°C to +32°C)
Refrigeration & cooling System	
Compressor Size	5.98cc
Charge	65g
Power consumption	350W
Cooling Power (24°C)	286W
Icebank	6Kg
Ice Bank Control	Eliwell/Dfx/Mechanical
Water Bath Capacity	15 litres
Recirculation Pump	Totten HPR6/11
Water & Product Coil Specification	
Number of product coils	0, (4 coil Pack available)
Product Coil Lengths (dia)	Each coil is 1.85m - (5/16")



Brandels - A Division of Booth Dispensers Limited
 Moor Park Avenue, Blackpool, Lancashire, FY2 0LZ
 T: +44 (0)1253 501800 - sales@brandels.co.uk