



- Customer driven design features
- First-class build quality, robust construction and attractive finish
- Designed-in performance enhancements to meet all working environments
- Improved access to components for easier maintenance and on-site servicing



**EXL950**  
Integral Soda  
Recirc Cooler

The EXL950 Air Cooled SR Cooler refrigeration system is designed for effective performance and improved energy efficiency.

With its largest-in-class 40-litre bath, the EXL950 develops an impressive 9.5 kg icebank reserve for optimum performance.

Built for durability and reliability, the EXL950 achieves optimum dispense-point temperatures by combining its efficient refrigeration system with a unique and optimised coil-pack design.

The EXL950 offers longer bath coils to maximise capacity and performance, and used a powerful Rotary Vane Procon Pump and Sisme Motor to recirculate the carbonated water more effectively and minimise heat absorption.

Dimensions & Weight	
Height	510 mm
Width (incl. handles)	775 mm
Depth (incl. spacer & overflow)	470 mm
Dry Weight	38 kg
Operating Parameters	
Electrical	230 V~ 50 Hz, 10 Amps
Ambient Temperature	5 °C to 32 °C
Refrigeration & Cooling System	
Compressor Size	16.0 cc
Refrigerant (& charge)	R134a (280 g)
Cooling Power	650 W
Condenser Fan Power	10 W
Icebank	9.5 kg
Water Bath Capacity	40 ltr
Recirculation Pump	Totton 10/15 or RV & Sisme
Water & Product Coil Specifications	
Python Pre-chill Coil Length (dia)	8.4 mtr (3/8")
Soda Pre-chill Coil Length (dia)	9.4 mtr (3/8")
Still Water Coil Length (dia)	3.9 mtr (5/16")
Number of Product Coils	4
Product Coil Lengths (dia)	2.4, 2.3, 2.2, 2.1 mtrs (5/16")

Options: Alternative Pump  
Rotary Vane Procon and 60w Sisme Motor or Totton 10/15 Mag-Drive



**Brandels - A Division of Booth Dispensers Limited**  
Moor Park Avenue, Blackpool, Lancashire, FY2 0LZ  
T: +44 (0)1253 501800 - sales@brandels.co.uk