

## SAFETY DATA SHEET FOOD SAFE LUBRICANT

### 1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

**PRODUCT NAME** FOOD SAFE LUBRICANT  
**PRODUCT NO.** EFSL400  
**APPLICATION** Lubricant  
**SUPPLIER** Booth Dispensers Ltd

+  
+  
info@hkw.co.uk

**EMERGENCY TELEPHONE** +44(0)1253 501800 between 8.30 am - 5.00pm Mon - Fri

### 2 HAZARDS IDENTIFICATION

Extremely flammable.

Repeated exposure may cause skin dryness or cracking.

**CLASSIFICATION** F+;R12. R66.

### 3 COMPOSITION/INFORMATION ON INGREDIENTS

Name	EC No.	CAS-No.	Content	Classification
PROPANE	200-827-9	74-98-6	30-60%	F+;R12
BUTANE	203-448-7	106-97-8	10-30%	F+;R12
C9-C12 Iso alkanes	292-459-0	90622-57-4	10-30%	Xn;R65. R66.
ISOBUTANE	200-857-2	75-28-5	10-30%	F+;R12

The Full Text for all R-Phrases are Displayed in Section 16

#### COMPOSITION COMMENTS

Ingredients not listed are classified as non-hazardous or at a concentration below reportable levels

### 4 FIRST-AID MEASURES

#### NOTES TO THE PHYSICIAN

Treat symptomatically

#### INHALATION

Move the exposed person to fresh air at once. Keep the affected person warm and at rest. Get prompt medical attention.

#### INGESTION

Rinse mouth thoroughly. Provide rest, warmth and fresh air.

#### SKIN CONTACT

Wash the skin immediately with soap and water. Get medical attention if any discomfort continues.

#### EYE CONTACT

Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.

### 5 FIRE-FIGHTING MEASURES

**FOOD SAFE LUBRICANT****EXTINGUISHING MEDIA**

Use: Powder. Dry chemicals, sand, dolomite etc. Water spray, fog or mist.

**SPECIAL FIRE FIGHTING PROCEDURES**

Containers close to fire should be removed or cooled with water. Use water to keep fire exposed containers cool and disperse vapours.

**UNUSUAL FIRE & EXPLOSION HAZARDS**

Aerosol cans may explode in a fire.

**6 ACCIDENTAL RELEASE MEASURES****SPILL CLEAN UP METHODS**

Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. Absorb in vermiculite, dry sand or earth and place into containers.

**7 HANDLING AND STORAGE****USAGE PRECAUTIONS**

Keep away from heat, sparks and open flame. Avoid spilling, skin and eye contact.

**STORAGE PRECAUTIONS**

Aerosol cans: Must not be exposed to direct sunlight or temperatures above 50°C.

**8 EXPOSURE CONTROLS/PERSONAL PROTECTION**

Name	Std	TWA - 8 hrs		STEL - 15 min		Notes
BUTANE	WEL	600 ppm	1450 mg/m3	750 ppm	1810 mg/m3	

WEL = Workplace Exposure Limit.

**INGREDIENT COMMENTS**

WEL = Workplace Exposure Limits

**PROTECTIVE EQUIPMENT****ENGINEERING MEASURES**

All handling to take place in well-ventilated area.

**RESPIRATORY EQUIPMENT**

No specific recommendation made, but respiratory protection must be used if the general level exceeds the Recommended Workplace Exposure Limit.

**HAND PROTECTION**

Use suitable protective gloves if risk of skin contact. The most suitable glove must be chosen in consultation with the gloves supplier, who can inform about the breakthrough time of the glove material.

**EYE PROTECTION**

Use eye protection.

**OTHER PROTECTION**

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact.

**HYGIENE MEASURES**

DO NOT SMOKE IN WORK AREA! Wash at the end of each work shift and before eating, smoking and using the toilet.

When using do not eat, drink or smoke.

**9 PHYSICAL AND CHEMICAL PROPERTIES**

<b>APPEARANCE</b>	Aerosol Liquid
<b>COLOUR</b>	Milky.
<b>ODOUR</b>	Solvent.
<b>SOLUBILITY</b>	Insoluble in water

REVISION DATE: SEPTEMBER 2008

**FOOD SAFE LUBRICANT**

<b>BOILING POINT (°C)</b>	65	<b>RELATIVE DENSITY</b>	0.760 @ 20 °c
<b>FLASH POINT (°C)</b>	<0 CC (Closed cup).	<b>AUTO IGNITION TEMPERATURE (°C)</b>	220
<b>FLAMMABILITY LIMIT - LOWER(%)</b>	1.9	<b>FLAMMABILITY LIMIT - UPPER(%)</b>	9.5

**10 STABILITY AND REACTIVITY****STABILITY**

Stable under normal temperature conditions.

**CONDITIONS TO AVOID**

Avoid heat, flames and other sources of ignition. Avoid contact with: Strong oxidising agents. Strong alkalis. Strong mineral acids.

**HAZARDOUS DECOMPOSITION PRODUCTS**

Fire creates: Vapours/gases/fumes of: Carbon monoxide (CO). Carbon dioxide (CO2).

**11 TOXICOLOGICAL INFORMATION****INHALATION**

High concentrations of vapours may irritate respiratory system and lead to headache, fatigue, nausea and vomiting. Vapours may cause headache, fatigue, dizziness and nausea. Prolonged inhalation of high concentrations may damage respiratory system.

**SKIN CONTACT**

Irritating to skin. Product has a defatting effect on skin. Prolonged contact may cause dryness of the skin.

**EYE CONTACT**

Irritating to eyes.

**Other Health Effects**

This substance has no evidence of carcinogenic properties.

**ROUTE OF ENTRY**

Inhalation.

**12 ECOLOGICAL INFORMATION****ECOTOXICITY**

Dangerous for the environment if discharged into watercourses.

**13 DISPOSAL CONSIDERATIONS****DISPOSAL METHODS**

Empty containers must not be burned because of explosion hazard. Dispose of waste and residues in accordance with local authority requirements.

**14 TRANSPORT INFORMATION**

<b>UK ROAD CLASS</b>	2		
<b>PROPER SHIPPING NAME</b>	AEROSOLS		
<b>UN NO. ROAD</b>	1950	<b>UK ROAD PACK GR.</b>	N/A
<b>ADR CLASS NO.</b>	2	<b>ADR CLASS</b>	Class 2: Gases
<b>ADR PACK GROUP</b>	N/A	<b>ADR LABEL NO.</b>	2.1
<b>CEFIC TEC(R) NO.</b>	20G5F	<b>RID CLASS NO.</b>	2
<b>RID PACK GROUP</b>	N/A	<b>UN NO. SEA</b>	1950
<b>IMDG CLASS</b>	2.1	<b>IMDG PACK GR.</b>	N/A
<b>EMS</b>	F-D, S-U	<b>MFAG</b>	See Guide
<b>MARINE POLLUTANT</b>	No.	<b>UN NO. AIR</b>	1950

**FOOD SAFE LUBRICANT**

AIR CLASS

2.1

AIR PACK GR.

N/A

**15 REGULATORY INFORMATION****SYMBOLS**

Extremely Flammable

**RISK PHRASES**

R12 Extremely flammable.  
R66 Repeated exposure may cause skin dryness or cracking.

**SAFETY PHRASES**

A1 Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.  
A2 Do not spray on a naked flame or any incandescent material.  
S2 Keep out of the reach of children  
S24 Avoid contact with skin.  
S16 Keep away from sources of ignition - No smoking.  
S37 Wear suitable gloves.  
S51 Use only in well-ventilated areas.

**UK REGULATORY REFERENCES**

Chemicals (Hazard Information &amp; Packaging) Regulations.

The Control of Substances Hazardous to Health Regulations 1988.

**ENVIRONMENTAL LISTING**

Rivers (Prevention of Pollution) Act 1961. Control of Pollution (Special Waste Regulations) Act 1980. Control of Pollution Act 1974.

**EU DIRECTIVES**

System of specific information relating to Dangerous Preparations. 2001/58/EC.

Dangerous Substance Directive 67/548/EEC.

Dangerous Preparations Directive 1999/45/EC.

Commission Directive 2000/39/EC of 8 June 2000 establishing a first list of indicative occupational exposure limit values in implementation of Council Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work.

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, including amendments.

**APPROVED CODE OF PRACTICE**

Classification and Labelling of Substances and Preparations Dangerous for Supply. Safety Data Sheets for Substances and Preparations.

**GUIDANCE NOTES**

Workplace Exposure Limits EH40.

**16 OTHER INFORMATION****REVISION COMMENTS**

Revised in accordance with CHIP3 and EU Directives 1999/45/EC and 2001/58/EC

**ISSUED BY**

Helen O'Reilly

**REVISION DATE**

SEPTEMBER 2008

**REV. NO./REPL. SDS**

5

**GENERATED**

### FOOD SAFE LUBRICANT

SDS NO. 11001

#### RISK PHRASES IN FULL

- R12 Extremely flammable.
- R65 Harmful: may cause lung damage if swallowed.
- R66 Repeated exposure may cause skin dryness or cracking.

#### DISCLAIMER

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.